



Bariatric Shower Trolley

TR 4000 Atlas

Hygiene Equipment
Designed for People



Generic Tender Specifications Bariatric Shower Trolley (450 kg/1000 lbs)

Specification for Shower Trolley (bariatric battery operated)

- The equipment is height-adjustable for the caregiver's ergonomic use and is specifically designed and manufactured for safe in-patient hospital use showering both bariatric and taller patients
- Equipment shall be delivered 100 % assembled and ready for use after charging the batteries
- Equipment to include soft and comfortable flame retardant mattress and head pillow and 1000 mm/39 inch flexible drainage hose
- Hand control operated for raising, lowering and tilting to enable a comfortable and safe working height for the caregiver
- Tilt control in both directions for fast "Trendelenburg" position and easy drainage
- Easy patient care width 180 degrees foldable side rails on both sides for easier access during patient transfer
- Stainless steel foldable side rails that locks into position for safe patient transfer and caregiver convenience
- Side rails must also be foldable inwards when passing through narrow doorways
- Shower trolley to be equipped with bumper wheels on all four corners for wall and doorway protection
- For tall patients (>1970 mm/77^{3/5} inch) head end rail can be folded to a horizontal position for extra stretcher length
- Compact base design to allow access under low bed frames
- The chassis height shall be (140 mm/5^{1/2} inch) to allow mobile sling lift transfers
- On board high capacity rechargeable batteries (min. 24 V, 7 Ah) to be charged via main supply
- Magnetic battery charger connection for safety and ease of use
- Mattress can be easily removed for cleaning and is flame retardant
- Foot controlled center locking castor brake system with straight steering
- Anti-corrosion treatment on all sheet metal parts and stainless steel construction on all active movable sheet metal parts
- Shower trolley designed for easy cleaning

Dimension and load specifications

- | | |
|------------------------------|-------------------------------------|
| • External Length: | max. 2210 mm/87 inch |
| • External Width: | max. 915 mm/36 inch |
| • Length Patient Work Area | min. 1970 mm/77 ^{3/5} inch |
| • Width Patient Working Area | min. 770 mm/30 ^{1/3} inch |
| • Height Range: | 535 - 835 mm/21 - 33 inch |
| • Max Patient Weight: | 450 kg/1000 lbs. |



TR EQUIPMENT